
(f)air tightness® GREEN



(f)air tightness® GREEN is the economical choice for taping air tightness membranes and vapour control layers. Its high performance adhesive system and excellent tack ensures a durable air tightness performance according to DIN 4108/7. (f)air tightness® GREEN is made for internal applications only.

The tape will bond to a wide range of materials in the construction business, like air tight & vapour control membranes, PE films, uPVC, metal, timber and sheeting products like plywood or OSB.
Some substrates may require a pre-treatment with primer.

Technical data sheet

PARAMETER	UNIT	VALUE
Durable air tight bonding performance	DIN 4108/11	passed
Reaction to fire	DIN EN 13501/1	class E
UV Resistance	[month]	>1
GEV-EMICODE		EC 1+ (very low emission)
Peel Adhesion	[N/25mm]	≥ 35
Elongation	[%]	100
Processing Temperature	[°C]	+5 to +35
Temperature Resistance	[°C]	-40 to +100
Storage Temperature	[°C]	+15 to +25*
Resistance against condensation		high
Carrier		reinforced LDPE film
Adhesive		acrylic dispersion
Colour		green
Dimension per roll		60mm x 25m

*The relative humidity level should be in a range of 40% - 60%

Contained information, advice and guidance is given, based on our knowledge, researches, experience and in good faith. We´re taking no responsibility for the consequences of improper or incorrect use of our products. Each user has to ensure in every possible way (including an examination of the final product in relevant conditions) the suitability of the selected material to achieve the objectives, pursued by the user.

© GBS 2022