
(f)air tightness® *BLACK*



(f)air tightness® BLACK is the most versatile tape for membranes in the construction business.
Its high performance adhesive system and excellent tack ensures a durable bonding performance according to DIN 4108/7 & 4108/11. (f)air tightness® BLACK is UV resistant and therefore for internal and external use .

The tape will bond to a wide range of materials in the construction business, like air tight, vapour control & breathable membranes, PE films, uPVC, metal, timber and sheeting products like plywood or OSB.
Some substrates may require a pre-treatment with primer.

MADE IN GERMANY FOR PERFECT AIR TIGHTNESS

According to DIN 4108-7 4108-11

Technical data sheet

PARAMETER	UNIT	VALUE
Durable air tight bonding performance	DIN 4108/11	passed
Reaction to fire	DIN EN 13501/1	class E
UV Resistance	[month]	>24
GEV-EMICODE		n.a.
Peel Adhesion	[N/25mm]	≥ 35
Elongation	[%]	300
Processing Temperature	[°C]	-10 to +35*
Temperature Resistance	[°C]	-40 to +100
Storage Temperature	[°C]	+15 to +25**
Resistance against condensation		high
Carrier		reinforced LDPE film
Adhesive		acrylic dispersion
Colour		black
Dimension per roll		60mm x 25m

* Processing temperatures below +5 degrees Celsius require special care for the application process.

** The relative humidity level should be in a range between 40% and 60%.

Contained information, advice and guidance is given, based on our knowledge, researches, experience and in good faith. We´re taking no responsibility for the consequences of improper or incorrect use of our products. Each user has to ensure in every possible way (including an examination of the final product in relevant conditions) the suitability of the selected material to achieve the objectives, pursued by the user.

© GBS 2022