(f)air tightness® WISA IN



(f)air tightness® WISA IN is a fully self-adhesive window tape for creating the required air tightness around windows and doors. Due to its vapour permeability, the tape has to be applied on the warm side of the thermal building envelope.
(f)air tightness® WISA IN can be used for taping to various substrates like block,brick, concrete, plaster, metal, timber, sheetings (OSB & plywood) and uPVC. Some substrates may require a pre-treatment with primer.

According to DIN 4108-7 4108-11

Technical data sheet

PROPERTY	STANDARD	VALUE
Air Permeability	DIN EN 12114	passed (>0.01m³/hm²)
Durable Air Tight Bonding Performance	DIN 4108-11	passed
Reaction to Fire	DIN EN 13501	Class E
Vapour Permeability (sd Value)	DIN EN 1931	approx. 30m
Tensile Strength	DIN EN 12311	170N/50mm (lengthwise) 120N/50mm (crosswise)
Adhesive Strength	DIN EN 1939	minimum 35N/25mm
Temperature Resistance		-40°C to +100°C
Application Temperature		+5°C to +40°C
Aging Resistance		very good
Carrier		synthetic fleece
Adhesive		solvent-free acrylic dispersion
Colour		white
Standard Dimensions		75/100/150/200/250mm x 25m

The tape should be stored at room temperature (20°C, 50% rel. humidity).

Contained information, advice and guidance is given, based on our knowledge, researches, experience and in good faith. We´re taking no responsibility for the consequences of improper or incorrect use of our products. Each user has to ensure in every possible way (including an examination of the final product in relevant conditions) the suitability of the selected material to achieve the objectives, pursued by the user.

© GBS 2022